



XLE

A Real Trailer
at a Real Value

STANDARD FEATURES

- 12" Aluminum Stone Guard
- Steel Unibody Construction
- Approximate 5' 6" Interior Height (5' and 6' wide)
- Approximate 4' Interior Height (4' wide)
- Approximate Exterior Width of 64" on 4' wide
80" on 5' wide, 92" on 6' wide
- Protective Undercoating
- 2" Coupler with Jack
- Single Tube Tongue (4' wide)
- Two Tube Tongue (5' and 6' wide)
- LED Surface Mounted Tail & Clearance Lights
- Safety Chains
- Aluminum Fenders
- 4-Way Trailer Plug (no brakes)
- Dexter Spring Axles with E-Z Lube Hubs
- Single Rear Door (4' and 5' wide)
- Double Rear Doors (6' wide)
- Luan Walls
- 24" On-Center Ceiling
- 24" On-Center Walls and Floor
- .030 Smooth Aluminum Exterior
- 3/4" square edge T-Grade OSB flooring
- 12" Bias Ply Tires (4' wide)
- 15" Radial Tires (5' and 6' wide)
- Screwed Exterior
- 3" Tube Frame
- (1) 12 Volt Dome Light with Switch
- 1 Year Warranty

Pricing

			SPRING AXLE
TRAILER WIDTH	TRAILER LENGTH	AXLES	Price
4'	6'	SA 20	
5'	8'	SA 30	
5'	10'	SA 30	
6'	10'	SA 30	
6'	12'	SA 30	

Additional Options

- Light Duty Ramp Door (No Flap)
- D Rings
- Rope Ties
- Extra Dome Light
- Roof Vent
- Tire Carrier
- Spare Tire
- TSR Vent
- Fold Down Stabilizer Jacks
- 3/8" Plywood Walls
- Side Door (NOT STANDARD on any XLE model)
- 24" Stone Guard

Trailers may be shown with optional features. We reserve the right to change specifications at any time, without incurring obligation.

Revised 1/1/17